

RG-NBS5100-24GT4SFP

Reyee Switch Cloud Capa 3

24 puertos RJ45 Gigabit

4 puertos SFP Gigabit

Static LAG/DHCP Snoop/IGMP

Snoop/Port Mirror

VLAN/Port

Isolation/STP/RSTP/ACL/QoS/802.1X

Servidor DHCP/Rutas

estáticas/RIP/OSPF/SNMP



Reyee

Switch de sobremesa Gestionable Capa 3

24 puertos RJ45 10/100/1000 Mbps + 4 Puertos SFP 10/100/1000 Mbps

Montaje en rack

Especificaciones

Interface	24 puertos RJ45 10/100/1000 Mbps + 4 Puertos SFP
Velocidad puertos	24x 10/100/1000 Mbps - 4 x SFP 10/100/1000 Mbps
VLAN	Hasta 4096 Voice VLAN
Protocolos y Tecnologías de Red	LLDP/LLDP-MED IGMP Snooping v1/v2 CPU Protect Policy Energy Efficient Ethernet ACL Jumbo Frame 9216 Static LAG LACP 802.1X
Protocolos L3	RIP OSPF Static Routing
Control de redundacia	Spanning Tree (STP, RTSP)
Protocolos Gestión	Web/Cloud/APP/SNMP
Alimentación	AC 100 V - 240 V
Temperatura de funcionamiento	0° C - 50° C
Dimensiones	267.5 (Fo) x 43.6 (Al) x 440 (An) mm
Peso	2,9 Kg (Con embalaje)