

RG-NBS3200-24SFP/8GT4XS

Reyee Switch Cloud Gestionable L2

24 puertos SFP + 8 Combo

RJ45/SFP + 4 SFP+

(24 + 8) 10/100/1000 Mbps + 4 SFP+

10 Gbps

VLAN/Port

Isolation/STP/RSTP/ACL/QoS

Static LAG/DHCP Snoop/IGMP

Snoop/Port Mirror

Enrackable



Reyee

Switch de sobremesa Gestionable Capa 2

24 puertos SFP Gigabit + 8 puertos Combo RJ45/SFP Gigabit + 4 Puertos SFP+ 10 Gbps

Montaje en rack

Especificaciones

Interface	24 puertos SFP Gigabit + 8 puertos Combo RJ45/SFP Gigabit + 4 Puertos SFP+ 10 Gbps
Velocidad puertos	Gigabit 24 puertos SFP + 8 Combo RJ45/SFP 10 Gbps 4 puertos SFP+
VLAN	Hasta 4096 Voice VLAN
Protocolos y Tecnologías de Red	LLDP/LLDP-MED IGMP Snooping v1/v2 CPU Protect Policy Energy Efficient Ethernet ACL Jumbo Frame 9216
Control de redundancia	Spanning Tree (STP, RTSP)
Protocolo Gestión	Web/Cloud/APP
Alimentación	AC 100 V - 240 V
Temperatura de funcionamiento	0° C - 50° C
Dimensiones	267.5 (Fo) x 43.6 (Al) x 440 (An) mm
Peso	3,35 Kg (Con embalaje)